

# **Material Safety Data Sheet**

# 1. Chemical Product and Company Identification

DESCRIPTION: ELMER'S STIX-ALL PRODUCT TYPE: SILICONE ELASTOMER

APPLICATION: E650.

# Manufacturer/Supplier Information

MSDS Prepared by:
Elmer's Products, Inc.
Emergency Phone Number

1000 Kingsmill Parkway
Columbus, OH 43229
For additional health, safety or regulatory information, call 614-225-7695.
Call 1-800-848-9400 to place an order or request additional MSDSs.

## 2. Composition, Information on Ingredients

The ingredients listed below have been associated with one or more immediate and/or delayed(\*) health hazards. Risk of damage and effects depends upon duration and level of exposure. BEFORE USING, HANDLING, OR EXPOSURE TO THESE INGREDIENTS, READ AND UNDERSTAND THE MSDS.

#### 3. Hazards Identification

## 3.1 Emergency Overview

Appearance Cloudy colored paste
Odor Acetic acid
CAUTION!
Not a significant fire hazard.
Overexposure may cause central nervous system depression. May cause irritation of nose, throat and lungs if allowed to become

## HMIS Rating

```
HEALTH = 1 (slight)
FLAMMABILITY = 0 (minimal)
REACTIVITY = 0 (minimal)
CHRONIC = *
```

#### 3.2 Potential Health Effects

#### Immediate Hazards

INGESTION: No hazards known to company.

INHALATION: Not expected to be harmful under normal conditions of

use. However, overexposure may cause central nervous system depression. Also, if allowed to become airborne,

may cause irritation of nose, throat and lungs.

SKIN: No hazards known to company. EYES: No hazards known to company.

#### Delayed Hazards

```
Silica 7631-86-9
Can cause lung fibrosis. Pre-existing respiratory disorders may be aggravated by exposure.
-- See Footnote C.
Footnote C: As of the date of issuance of this document, this material has not been listed by NTP, classified by IARC nor regulated by OSHA as a carcinogen.
```

#### 4. First Aid Measures

INGESTION: If accidentally swallowed, dilute by drinking large

quantities of water. Immediately contact poison control

center or hospital emergency room for any other

additional treatment directions.

INHALATION: Remove to fresh air.

EYES: Immediately flush eyes with plenty of water. Call a

physician if irritation persists.

#### 5. Fire Fighting Measures

Autoignition Temperature Not available
Upper/Lower Flammable Limits Not applicable
Up/Lower Explosive Limits, % by Vol Not applicable
Flash Point Not applicable
Will not burn unless water has evaporated. Dried material may burn.
In case of fire, water should be used to keep fire-exposed containers cool.

#### 6. Accidental Release Measures

Sweep (scoop) up and remove to a chemical disposal area. Prevent entry into natural bodies of water.

#### 7. Handling and Storage

# 7.1 Handling

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).

INHALATION: Avoid prolonged or repeated breathing of vapor.

## 7.2 Storage

Store in a cool, dry place.
Keep containers tightly closed.
Exposure to small amounts of moisture, even moisture in air, causes polymerization and renders the product unusable.

## 8. Exposure Controls/Personal Protection

#### 8.1 Exposure Controls

If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

#### 8.2 Personal Protection

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance with OSHA laws and regulations or other applicable standards or guidelines, including ANSI standards regarding respiratory protection.

# 8.3 Exposure Guidelines

7631-86-9 Silica

ACGIH TLV: 10 mg/m³ TWA (as Amorphous silica)

OSHA PEL: 20 mppcf; 80/(%SiO2) mg/m³ TWA (as Amorphous

REMANDED PEL: 6 mg/m³ TWA (as Amorphous silica) OSHA 1989 PEL remanded, but in effect in some states

# 9. Physical and Chemical Properties

Percent Volatiles

pH @ 25 C Not available

Specific Gravity 1.08

Appearance Cloudy colored paste

Autoignition Temperature Not available Not applicable Boiling Point

Vapor Density (Air=1) > 1

Vapor Pressure, mm Hg @ 20 C Not applicable Evaporation Rate (Butyl Acetate=1) Not applicable Upper/Lower Flammable Limits Not applicable Up/Lower Explosive Limits, % by Vol Not applicable Flash Point Not applicable Freezing Point Not available Acetic acid Odor Odor Threshold, ppm Not available

Negligible Solubility in Water Coefficient of Water/Oil Distrib. Not available

# 10. Stability and Reactivity

Normally stable as defined in NFPA 704-12(4-3.1).

# Incompatibilities:

None known to company.

## · Decomposition products may include:

Oxides of carbon and silicon.

## Hazardous polymerization:

Will not occur.

#### Other Hazards:

Liberates acetic acid on curing.

## 11. Toxicological Information

INGESTION: Not toxic orally when tested as described in 16 CFR Part

1500.3 (c)(1) and (2).

INHALATION: Not toxic by inhalation when tested as described in 16

CFR Part 1500.3 (c) (1) and (2).

SKIN Not toxic dermally when tested as described in 16 CFR

ABSORPTION: Part 1500.3 (c)(1) and (2).

SKIN: Not an irritant when tested as described in 16 CFR Part

1500.41.

EYES: Not an irritant when tested as described in 16 CFR

Part 1500.42.

Silica 7631-86-9 LC50: Not available

LD50: orl-rat=3160 mg/kg (RTECS)

#### 12. Ecological Information

Not determined.

# 13. Disposal Considerations

Dispose of according to local, state/provincial, and federal requirements.

# 14. Transport Information

## 14.1 U.S. Department of Transportation (DOT)

The data provided in this section is for information only and may not be specific to your package size. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Non-Regulated.

#### 14.2 Canadian Transportation of Dangerous Goods (TDG)

Non-Regulated.

## 15. Regulatory Information (Selected Regulations)

#### 15.1 U.S. Federal Regulations

#### OSHA Hazard Communication Standard 29CFR1910.1200

This material presents possible health hazards as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29 CFR Part 1910.1200 "Hazard Communication" Standard.

## • SARA Title III: Section 311/312

Delayed health hazard

#### SARA Title III Section 313 and 40 CFR Part 372

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.

None required per SARA TITLE III SECTION 313.

#### TSCA Section 8(b) Inventory

All reportable chemical substances are listed on the TSCA Inventory. We rely on certifications of compliance from our suppliers for chemical substances not manufactured by us.

# 15.2 Canadian Regulations

#### Workplace Hazardous Materials Information System (WHMIS)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR.

CLASS D, DIV 2B

# Canadian Environmental Protection Act (CEPA)

All reportable chemical substances are listed on the Domestic Substances List (DSL) or otherwise comply with CEPA new substance notification requirements.

## National Pollutant Release Inventory (NPRI)

This product contains the following chemical(s) subject to the reporting requirements of the Canadian Environmental Protection Act (CEPA) subsection 16(1), National Pollutant Release Inventory. None required.

#### 16. Other Information

HL (Cautions Required): Products bearing the HL Health Label (Cautions Required) Seal of The Art & Creative Materials Institute, Inc. (ACMI) are certified to be properly labeled in a program of toxicological evaluation by a medical expert. This program is reviewed by ACMI's Toxicological Advisory Board. These products are certified by ACMI to be labeled in accordance with the chronic hazard labeling standard, ASTM D-4236 and Federal Law, P.L. 100-695.

#### User's Responsibility

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Educate and train your workers regarding OSHA and WHMIS precautions. Instruct your

workers to handle this product properly. Consult with appropriate experts to guard against hazards associated with use of this product and its ingredients.

#### Disclaimer

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. No claim of any kind shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

CUR ISSUE 05-NOV-04
PREVIOUS ISSUE: 14-SEP-01